

| # | Machine Description | Clamp Tons | Shot Size | Machine Controller | Tie Bar Clearance | | Mold Height | | Max Clamp Stroke | Open Max | Eject Stroke |
|----|-------------------------|------------|-----------|--------------------|-------------------|----------|-------------|-------|------------------|----------|--------------|
| | | | | | Horizontal | Vertical | Min | Max | | | |
| 1 | Engle ES 80/85 | 80 | 1.2 | CC-80 | 13.6 | 13.6 | 5.9 | 14.9 | 11.74 | 26.7 | 3.94 |
| 2 | Engle ES 80/30 | 30 | 1.2 | CC-100 | 10.23 | 10.23 | 5.91 | 18.89 | | 18.89 | 2.75 |
| 3 | Engle ES 240/80 | 83 | 6.7 | EC-88 | 13.6 | 13.6 | 5.9 | 14.9 | 11.74 | 26.7 | 9.94 |
| 4 | Arburg 305 ECO | 77 | 5.6 | Dialogica | 12 | 5.3 | 7.9 | 15.7 | 9.85 | 25.6 | 2.75 |
| 5 | Arburg 305 ECO | 77 | 3.7 | Dialogica | 12 | 5.3 | 7.9 | 15.7 | 9.85 | 25.6 | 2.75 |
| 6 | Arburg 305 ECO | 77 | 3.7 | Dialogica | 12 | 5.3 | 7.9 | 15.7 | 9.85 | 25.6 | 2.75 |
| 7 | Arburg 305 ECO | 77 | 3.7 | Dialogica | 12 | 5.3 | 7.9 | 15.7 | 9.85 | 25.6 | 2.75 |
| 8 | Arburg 305 ECO | 77 | 3.7 | Dialogica | 12 | 5.3 | 7.9 | 15.7 | 9.85 | 25.6 | 2.75 |
| 9 | Engle TL 750/200 | 200 | 15.4 | EC-100 | | | 9.84 | | 27.56 | | 5.9 |
| 10 | Engle TL 1050/200 | 200 | 19.6 | EC-100 | | | 9.84 | | 27.56 | | 5.9 |
| 11 | Engle ES 600/150 | 150 | 10.3 | CC-90 | 19.69 | 16.54 | 5.91 | 20.47 | 16.54 | 37.01 | 5.12 |
| 12 | Engle ES 650/150 | 150 | 12.7 | CC-100 | 19.69 | 16.54 | 5.91 | 20.47 | 16.54 | 37.01 | 5.12 |
| 13 | Engle ES 600/150 | 150 | 10 | CC-90 | 19.69 | 16.54 | 5.91 | 20.47 | 16.54 | 37.01 | 5.12 |
| 14 | Cincinnati RoboShot 330 | 385 | 31.4 | Fanuc CNC | 28 | 28 | 11.8 | 25.6 | 23.6 | 49.21 | 5.91 |
| 15 | Cincinnati RoboShot 330 | 385 | 31.4 | Fanuc CNC | 28 | 28 | 11.8 | 25.6 | 23.6 | 49.21 | 5.91 |
| 16 | Engle ES 1300/300 | 300 | 24.8 | CC-90 | 25.04 | 25.04 | 7.87 | 25.98 | 23.62 | 49.6 | 7.87 |
| 17 | Engle ES 1300/300 | 300 | 24.8 | CC-90 | 25.04 | 25.04 | 7.87 | 25.98 | 23.62 | 49.6 | 7.87 |
| 18 | Engle ES 1300/300 | 300 | 24.8 | EC-88 | 25.04 | 25.04 | 7.87 | 25.98 | 23.62 | 49.6 | 7.87 |
| 19 | Engle ES 1300/300 | 300 | 24.8 | CC-90 | 25.04 | 25.04 | 7.87 | 25.98 | 23.62 | 49.6 | 7.87 |
| 20 | Cincinnati RoboShot 330 | 330 | 27.8 | Fanuc CNC | 28 | 28 | 11.8 | 25.6 | 23.6 | 49.21 | 5.91 |
| 21 | Engle ES 2050/400 | 400 | 38.7 | EC-100 | 30 | 30 | 11.81 | 33.94 | 27.56 | 61.5 | 9.45 |
| 22 | Engle ES 2000/400 | 400 | 38.7 | CC-100 | 30 | 30 | 11.81 | 33.94 | 27.56 | 61.5 | 9.45 |
| 23 | Arburg 270S-250-60 | 28 | 0.6 | Selogica | 10.63 | 10.63 | 7.87 | 15.67 | * | 15.67 | 3.74 |
| 24 | Arburg 270S-250-60 | 28 | 0.6 | Selogica | 10.63 | 10.63 | 7.87 | 15.67 | * | 15.67 | 3.74 |
| 25 | Arburg 270S-250-60 | 28 | 1.5 | Selogica | 10.63 | 10.63 | 7.87 | 15.67 | * | 15.67 | 3.74 |
| 26 | Arburg 270S-250-60 | 28 | 1.5 | Selogica | 10.63 | 10.63 | 7.87 | 15.67 | * | 15.67 | 3.74 |
| 27 | Engle ES 240/80 | 85 | 5.2 | EC-88 | 15.98 | 13.62 | 5.91 | 14.96 | 11.81 | 26.7 | 3.74 |
| 28 | Engle ES 600/150 | 150 | 10.3 | EC-100 | 19.69 | 16.54 | 5.91 | 20.47 | 16.54 | 37.01 | 5.12 |
| 29 | Engle ES 600/150 | 150 | 10.3 | EC-100 | 19.69 | 16.54 | 5.91 | 20.47 | 16.54 | 37.01 | 5.12 |
| 30 | Engle ES 2050/400 | 400 | 38.7 | EC-100 | 30 | 30 | 11.81 | 33.94 | 27.56 | 61.5 | 9.45 |
| 31 | Mitsubishi | 170 | | | | | | | | | |
| 32 | Mitsubishi | 230 | | | | | | | | | |
| C1 | Engle E-Motin | 65 | 2.5 | | N/A | N/A | | | | | |
| C2 | Engle E-Motin | 65 | | | N/A | N/A | | | | | |
| C4 | Engle E-Motin | 165 | 5.5 | | N/A | N/A | | | | | |
| C5 | Engle E-Motin | 165 | | | N/A | N/A | | | | | |

* On a hydraulic clamp machine, max clamp stroke will be max mold height minus actual mold height.